

Dye Sublimation Fabric  
Media Application Chart



	<u>Monaco HD</u>	<u>Techno HD</u>	<u>Vento HD</u>	<u>Bellagio HD</u>	<u>Torino HD</u>	<u>Tuscany HD</u>	<u>Supreme HD</u>	<u>Paris II HD</u>	<u>Satin HD</u>	<u>Bloccato HD</u>
<b>Banners</b>	X	X	X	X			X		X	X
<b>Tension Fabric Displays</b>					X	X				
<b>Tents</b>							X			
<b>Domes &amp; Pavillions</b>			X				X			
<b>Umbrellas</b>										
<b>Flags</b>	X	X	X							
<b>Flexi Signs</b>				X						
<b>Table Skirts</b>				X						
<b>Backdrops</b>	X	X	X	X			X			X
<b>Scenic</b>	X	X	X	X			X			
<b>Fence Covers</b>		X		X			X			
<b>Fabric Frames</b>					X	X				
<b>Backlit Frames</b>								X		
<b>Trade Show Booths</b>				X	X	X		X		

<u>Specifications</u>	<u>Monaco HD</u>	<u>Techno HD</u>	<u>Vento HD</u>	<u>Bellagio HD</u>	<u>Torino HD</u>	<u>Tuscany HD</u>	<u>Supreme HD</u>	<u>Paris II HD</u>	<u>Satin HD</u>	<u>Bloccato HD</u>
<b>Maximum Width</b>	122"- 3.1 m	122"- 3.1 m	122"- 3.1 m	126"- 3.2 m	126"- 3.2 m	126"- 3.2 m	122"- 3.1 m	124"- 3.15 m	122"- 3.1 m	118"- 3 m
<b>Elasticity</b>	N/A	N/A	N/A	N/A	3%	10%	N/A	2%	N/A	N/A
<b>Polyester Fibre</b>	100%	100%	100%	100%	100%	93%	100%	100%	100%	100%
<b>Blockout</b>										X
<b>Weight</b>	3.2 oz/yd2 -108 g/m2	3.4 oz/yd2 - 115 g/m2	3.2 oz/yd2 - 108 g/m2	6.5 oz/yd2 - 220 g/m2	6.3 oz/yd2 - 214 g/m2	6.8 oz/yd2 - 231 g/m2	9.7 oz/yd2 - 329 g/m2	7.7 oz/yd2 - 261 g/m2	6 oz/yd2 - 203 g/m2	6.9 oz/yd2 - 234 g/m2
<b>Fire rated NFPA 701*</b>	X	X	X	X	X	X	X	X	X	X
<b>Water Repellent</b>							X			
<b>Application</b>										
<b>Indoor</b>	X	X	X	X	X	X	X	X	X	X
<b>Outdoor **</b>	X	X	X				X			
<b>Ink Type</b>										
<b>Water-based</b>	X	X	X	X	X	X	X	X	X	X
<b>Green Characteristics</b>										
<b>Recyclable</b>	X	X	X	X	X	X	X	X	X	X
<b>Biodegradable</b>	X	X	X	X	X	X	X	X	X	X

\* NFPA 701 (USA) Certificate

\*\* Either because of its water repellency coating or its quick drying time

**Rigid Media I  
Media Application Chart**



	<u>Coroplast</u>	<u>Sintra</u>	<u>Foamcore</u>	<u>Styrene</u>	<u>Cardstock</u>	<u>Gator</u>
<b>POP Displays</b>	X	X	X	X	X	X
<b>Exhibits &amp; Kiosks</b>		X	X	X	X	X
<b>Backlit Frames</b>				X		
<b>Floor Graphics</b>						

<u>Specifications</u>	<u>Coroplast</u>	<u>Sintra</u>	<u>Foamcore</u>	<u>Styrene</u>	<u>Cardstock</u>	<u>Gator</u>
<b>Sheet Sizes*</b>	48" x 96" - 1.2 m x 2.4 m 48" x 120" - 1.2 m x 3 m	48" x 96" - 1.2 m x 2.4 m 60" x 120" - 1.5 m x 3 m	48" x 96" - 1.2 m x 2.4 m	48" x 96" - 1.2 m x 2.4 m 50" x 100" - 1.3 m x 2.5 m	45" x 65" - 1.1 m x 1.7 m 49" x 97" - 1.2 m x 2.5 m	48" x 96" - 1.2 m x 2.4 m 60" x 120" - 1.5 m x 3 m
<b>Thicknesses</b>	5/32" - 4 mm 25/64" - 10 mm	1/8" - 3mm 1/4" - 6 mm	3/16" - 5 mm	1/4" - 20 pt. 17/64" - 30 pt. 13/32" - 40 pt. 9/16" - 40 pt. 53/64" - 60 pt.	1/64" - 12 pt. 1/4" - 18 pt. 21/64" - 24 pt. 27/64" - 30 pt. 9/16" - 40 pt. 11/16" - 50 pt.	3/16" - 5mm 1/2" - 12.7 mm

<u>Lifetime</u>						
<b>Short-Term</b>	X		X			
<b>Medium-Term</b>		X			X	X
<b>Long-Term</b>				X		

<u>Application</u>						
<b>Indoor</b>	X	X	X	X	X	X
<b>Outdoor**</b>	X			X		

<u>Ink Type</u>						
<b>UV</b>	X	X	X	X	X	X

\* Other sizes available  
\*\* Either because of its water repellency coating or its quick drying time

**Rigid Media II  
Media Application Chart**



	<u>Dibond</u>	<u>PETG</u>	<u>Acrylic</u>	<u>Corrugate</u>	<u>ABS</u>	<u>G-Floor</u>
<b>POP Displays</b>	X	X		X		
<b>Exhibits &amp; Kiosks</b>	X		X			
<b>Backlit Frames</b>			X			
<b>Floor Graphics</b>						X

<u>Specifications</u>	<u>Dibond</u>	<u>PETG</u>	<u>Acrylic</u>	<u>Corrugate</u>	<u>ABS</u>	<u>G-Floor</u>
<b>Sheet Sizes*</b>	48" x 96" - 1.2 m x 2.4 m 60" x 120" - 1.5 m x 3 m	48" x 96" - 1.2 m x 2.4 m	49" x 97" - 1.2 m x 2.5 m 75" x 100" - 1.9 m x 2.5 m	Custom	48" x 96" - 1.2 m x 2.4 m	Custom
<b>Thicknesses</b>	1/8" - 3mm	17/64" - 20 pt. 27/64" - 30 pt. 9/16" - 40 pt. 53/64" - 60 pt. 1 1/4" - 90 pt. 1 41/64"- 118 pt	5/64" - 2mm 3/64" - 3mm 3/16" - 4mm 3/8" - 9mm 1/2" - 12mm	B-Flute/1/16" - 1.6mm E-Flute-1/8" - 3.2mm	1/4" - 18 pt. 17/64" - 20 pt. 27/64" - 30 pt. 9/16" - 40 pt. 53/64" - 60 pt.	1 3/8" - 35 mm 2 61/64" - 75mm

<u>Lifetime</u>						
<b>Short-Term</b>				X		
<b>Medium-Term</b>		X			X	
<b>Long-Term</b>	X		X			X
<b>Application</b>						
<b>Indoor</b>	X	X	X	X	X	X
<b>Outdoor**</b>	X		X		X	
<b>Ink Type</b>						
<b>UV</b>	X	X	X	X	X	X

\* Other sizes available  
\*\* Either because of its water repellency coating or its quick drying time

Roll Media  
Media Application Chart



	<u>Flex Vinyl</u> <u>7oz.</u>	<u>Flex Vinyl</u> <u>13oz.</u>	<u>BioFlex Vinyl</u> <u>15oz.</u>	<u>B/O Vinyl</u> <u>18oz.</u>	<u>PET B/O</u> <u>15oz.</u>	<u>DSS B/O</u> <u>14oz.</u>	<u>Mesh Vinyl-8oz</u> <u>(37% Air Flow)</u>	<u>Speaker Mesh</u> <u>(70% Air Flow)</u>
<b>Banners</b>	X	X	X	X	X	X	X	X
<b>Retractables</b>					X	X		
<b>Backlit Frames</b>								
<b>Building Wraps</b>	X	X					X	X
<b>Display Systems</b>	X	X	X	X	X			
<b>POP Stands</b>	X	X		X	X	X		
<b><u>Specifications</u></b>	<b><u>Flex Vinyl</u> <u>7oz.</u></b>	<b><u>Flex Vinyl</u> <u>13oz.</u></b>	<b><u>BioFlex Vinyl</u> <u>15oz.</u></b>	<b><u>B/O Vinyl</u> <u>18oz.</u></b>	<b><u>PET B/O</u> <u>15oz.</u></b>	<b><u>DSS B/O</u> <u>14oz.</u></b>	<b><u>Mesh Vinyl-8oz</u> <u>(37% Air Flow)</u></b>	<b><u>Speaker Mesh</u> <u>(70% Air Flow)</u></b>
<b>Maximum Width</b>	196" - 5 m	196" - 5 m	196" - 5 m	196" - 5 m	126" - 3.2 m	80" - 2 m	196" - 5 m	196" - 5 m
<b>Flame Resistant NFPA 701*</b>		X	X	X	X	X	X	X
<b>Double-Sided</b>				X	X			
<b><u>Applications</u></b>								
<b>Indoor</b>	X	X	X	X	X	X	X	X
<b>Outdoor **</b>	X	X	X	X	X	X	X	X
<b><u>Ink Types</u></b>								
<b>Solvent</b>	X	X	X	X	X	X	X	X
<b>UV</b>	X	X	X	X	X			X
<b>Latex</b>	X	X	X	X	X	X		

\* NFPA 701 (USA) Certificate

\*\* Either because of its water repellency coating or quick drying time

Roll Media II  
Media Application Chart



	<u>Backlit Vinyl</u>	<u>Artex Canvas</u>	<u>B/O Paper</u>	<u>Wallpaper</u>	<u>MXM</u>	<u>MXM B/O</u>	<u>Magnetic</u>	<u>BL Film</u>	<u>Poster Paper</u>
<b>Banners</b>		X			X				
<b>Panneaux Publicitaires</b>									
<b>Retractable Banner Stands</b>						X			
<b>Posters</b>			X		X				X
<b>Backlit Frames</b>	X				X			X	
<b>Building Wraps</b>									
<b>Display Systems</b>		X			X				
<b>POP Stands</b>	X	X	X	X	X		X	X	X

<u>Specifications</u>	<u>Backlit Vinyl</u>	<u>Artex Canvas</u>	<u>B/O Paper</u>	<u>Wallpaper</u>	<u>MXM</u>	<u>MXM B/O</u>	<u>Magnetic</u>	<u>BL Film</u>	<u>Poster Paper</u>
<b>Maximum Width</b>	196" - 5m	126" - 3.2 m	60" - 1.5 m	54" - 1.4 m	60" - 1.5 m	60" - 1.5 m	40" - 1 m	86" - 2.2 m	60" - 1.5 m
<b>Flame Resistant NFPA 701*</b>	X								
<b>Double-Sided</b>			X		X	X			
<b>Application</b>									
<b>Indoor</b>	X	X	X	X	X	X	X	X	X
<b>Outdoor**</b>	X						X		
<b>Ink Types</b>									
<b>UV</b>	X	X	X		X	X	X	X	X
<b>Latex</b>	X	X		X				X	

\* NFPA 701 (USA) Certificate

\*\* Either because of its water repellency coating or its quick drying time

Pressure Sensitive Media  
Media Application Chart



	<u>IJ180CV3</u>	<u>IJ3650-114</u> <u>Clear</u>	<u>IJ8624</u>	<u>Prosol Perf</u>	<u>Sigmax Perf</u>	<u>Window Call II</u> <u>Clear</u>	<u>Window Cal III</u> <u>Opaque</u>
Vehicle Wraps	X			X			
Window Adhesives	X	X			X	X	X
Floorb Graphics							
Backlit Frames							
Wall Murals / POP Stands	X						
Brick Walls			X				

<u>Specifications</u>	<u>IJ180CV3</u>	<u>IJ3650-114</u> <u>Clear</u>	<u>IJ8624</u>	<u>Prosol Perf</u>	<u>Sigmax Perf</u>	<u>Window Call II</u> <u>Clear</u>	<u>Window Cal III</u> <u>Opaque</u>
Maximum Widths	54"/60" - 1.4/1.5 m	54"/60" - 1.4/1.5 m	54" - 1.4 m	54" - 1.4 m	54"/60" - 1.4/1.5 m	54" - 1.4 m	54" - 1.4 m
Permanent		X	X	X	X		X
Removable	X					X	
<u>Applications</u>							
Indoor	X	X	X	X	X	X	X
Outdoor *	X		X				
<u>Ink Types</u>							
UV	X	X	X	X	X	X	X
Latex	X	X	X	X	X	X	X

\*Either because of its water repellency coating or its quick drying time

Pressure Sensitive Media II  
Media Application Chart



	<u>Classic Matte Low Tack</u>	<u>Ultra Trans. Removable</u>	<u>Classic Matte Rem. BO</u>	<u>Classic Matte BO</u>	<u>Wall Action</u>	<u>FabriTac</u>	<u>Ultimate Brick Wall Action</u>	<u>Arlon DPF</u>
<b>Vehicle Wraps</b>								
<b>Window Adhesives</b>			X			X		
<b>Floor Graphics</b>	X		X					
<b>Backlit Frames</b>		X						
<b>Wall Murals / POP Stands</b>			X	X	X	X		X
<b>Brick Walls</b>							X	

Specifications

<b>Maximum Width</b>	54" - 1.4 m	54"/60" - 1.4/ 1.5 m	54"/60" - 1.4/ 1.5 m	54"/60" - 1.4/ 1.5 m	54"/60" - 1.4/ 1.5 m	50"/54"/60" - 1.3/1.4/1.5 m	54" - 1.4 m	54"/60" - 1.4/ 1.5 m
<b>Permanent</b>				X				X
<b>Removable</b>	X	X	X		X	X	X	

Applications

<b>Indoor</b>	X	X	X	X	X	X	X	X
<b>Outdoor *</b>				X				X

Ink Types

<b>UV</b>	X	X	X	X	X	X	X	X
<b>Latex</b>	X	X	X	X	X	X	X	X

\* Either because of its water repellency coating or its quick drying time

Eco Verde  
Media Application Chart



	<u>Poly Pro 3000</u>	<u>4/4 Blockout 13 oz.</u>	<u>Black Back 13 oz.</u>	<u>Banner 6.9 oz.</u>
<b>Banners</b>	X	X	X	X
<b>Display Frame Systems</b>	X	X	X	X
<b>POP Stands</b>	X	X		
<b>Art Reproductions</b>			X	

<u>Specifications</u>	<u>Poly Pro 3000</u>	<u>4/4 Blockout 13 oz.</u>	<u>Black Back 13 oz.</u>	<u>Banner 6.9 oz.</u>
<b>Maximum Width</b>	126" - 3.2 m	126" - 3.2 m	126" - 3.2 m	126" - 3.2 m
<b>Weight</b>	8.8 oz/yd2 - 298 g/m2	11.8 oz/yd2 - 400g/m2	9.7 oz/yd2 -329 g/m2	6.9 oz/yd2 - 234 g/m2
<b>Fire rated NFPA 701*</b>	X	X	X	X
<b>Crease Resistant</b>		X	X	X
<b>Opaque</b>		X	X	X
<b>Double-Sided Print</b>		X		

Applications

<b>Indoor</b>	X	X	X	X
<b>Outdoor **</b>	X	X	X	X

Ink Type

<b>Latex</b>	X	X	X	X
--------------	---	---	---	---

Green Characteristics

<b>Recyclable</b>	X	X	X	X
<b>Recyclable Code</b>	5	1	1	1
<b>Biodegradable</b>	X	X	X	X
<b>PVC Free</b>	X	X	X	X

\* NFPA 701 (USA) Certificate

\*\* Either because of its water repellency coating or its quick drying time